

## Production of Ethanol from Biomass Using Dicarboxylic Acids

**Track Code:** 64990

**Categories:**

- Chemical Engineering
- Chemistry and Chemical Analysis

**Keywords:**

- Biofuels
- Chemical Engineering
- Clean Energy
- Ethanol
- Green Technology

In 2005, the U.S. government created the Renewable Fuel Standard (RFS) program, which was further expanded in 2007 with the Energy Independence and Security Act (EISA). Both programs mandate reducing greenhouse gas emissions, expanding renewable fuel sources, and reducing reliance on imported oil, resulting in increased emphasis on developing new methods to efficiently produce fuel from renewable, non-petroleum resources.

Ethanol, a renewable fuel, is commercially produced from feedstocks of cornstarch, sugar cane, and sugar beets; however, these products have competing uses in the food industry, which increases their price and leads to seeking alternative feedstock sources. Current processes use acids, which cause degradation of minerals in the biomass to form substances that can inhibit the subsequent fermentation steps, increasing the cost of such processes.

Researchers at Purdue University have developed a process for converting lignocellulosic biomass to ethanol that results in an ethanol yield of approximately 90 percent. This process includes treating lignocellulosic biomass with a dicarboxylic acid to hydrolyze hemicellulose and lignocellulosic biomass to xylose. This results in minimal formation of degradation products. Lower amounts of degradation product allows for less enzymes or yeast used, resulting in a ready fermentation of the xylose to ethanol using a yeast without the necessity of purifying material.

**Advantages:**

- Minimal degradation in ethanol production
- Decreases the number of enzymes or yeast used in the fermentation of ethanol

**Potential Applications:**

- Biofuels
- Ethanol production
- Alternative fuel production

**People:**

- Ladisch, Michael R (Project leader)
- Mosier, Nathan Scott
- Spindler, Brad
- Stater, Brian
- Wyman, Charles

**Intellectual Property:**

**Application Date:** October 13, 2010

**Type:** NATL-Patent

**Country of Filing:** Canada

**Patent Number:** 2,776,717

**Issue Date:** February 28, 2017

**Application Date:** October 13, 2010

**Type:** NATL-Patent

**Country of Filing:** China

**Patent Number:** CN ZL201080046974.3

**Issue Date:** December 7, 2016

**Application Date:** April 13, 2012

**Type:** Utility Patent

**Country of Filing:** United States

**Patent Number:** 8,790,904

**Issue Date:** July 29, 2014

**Application Date:** October 13, 2010

**Type:** PCT-Patent

**Country of Filing:** WO

**Patent Number:** (None)

**Issue Date:** (None)

**Application Date:** October 13, 2010

**Type:** NATL-Patent

**Country of Filing:** Brazil

**Patent Number:** (None)

**Issue Date:** (None)

**Application Date:** October 13, 2009

**Type:** Provisional-Patent

**Country of Filing:** United States

**Patent Number:** (None)

**Issue Date:** (None)

**Contact OTC:**

Purdue Office of Technology Commercialization  
The Convergence Center  
101 Foundry Drive, Suite 2500  
West Lafayette, IN 47906

Phone: (765) 588-3475

Fax: (765) 463-3486

Email: [otcip@prf.org](mailto:otcip@prf.org)